靈	TO	W	N	验 公 富司
	FOOD SERVIC	E EQUIPMEN	T CO., INC	
800/2 718/3	221.5032 388.5650 718/388.5860	customerservice@tov	wnfood.com	www.townfood.com

Item Number	
Project	
Quantity	



AUTOQUOTES

Electronic Rice Cookers







Models

56822 25 Cup1 120v Electronic rice cooker 56824 25 Cup1 230v Electronic rice cooker 57137 37 Cup1 120v Electronic rice cooker 57138 37 Cup1 230v Electronic rice cooker 57155 55 Cup1 230v Electronic rice cooker

General

Cook and serve from the same unit. Automatically cooks rice to perfection and keeps it hot for serving. The insulated double wall body has heating elements to more evenly warm rice than a bottom heat only rice cooker. The hinged, heated cover reduces heat loss. The attractive stainless steel exterior is easy to clean. Made by Town in the USA with industrial components.

RiceMasters will cook different kinds of rice. Our owner's manual provides a good guide. With practice, you will perfect the correct proportions of rice to water for your preferred type of rice. Steamed rice is only the beginning–recipes are included in the manual for rice pilaf, jambalaya, sweet rice and mexican rice.

Standard features

- Durable reinforced body, extra-thick heater plate and water resistant controller gives longer unit life.
- Overheat protection—The high limit control prevents heating element damage or failure due to a dented pot.
- Touch controls and Indicator lights-first touch the ON/OFF button and the unit turns on in the hold mode. Both the power and the hold
 indicator lights will illuminate. A touch to the PRESS TO COOK button starts the cook cycle. The hold light will go out and the cook light will
 illuminate. When the rice is cooked the cook light will go out and the hold light will illuminate, indicating the rice is cooked. Unit stays in
 hold mode until turned off or another cook cycle is started. Touch the power button at any time to turn the unit off.
- Electronic Cook and Hold operation—Touch the button, walk away for perfect rice every time Anelectronic sensor detects when the water
 has been absorbed to end the cook cycle. RiceMaster switches to
 holdautmatically when cooking is done. Rice will be held at an NSF
 compliant 150° F. Holding time should not exceed 2 hours.
- 1/8" thick lift out rice pot resists dents, removable for washing rice and cleaning.
- Capacity is in Asian cups-rice cooker capacity in Asia is measured by 6 ounce (by volume) cups of raw rice. Town RiceMasters use that standard. We also provide capacity by weight on chart on right page.
- Commercial ETL and NSF listed-large capacity rice cookers designed and built for commercial use.
- Auto-reset overheat protection.
- 2 year mail in warranty starts from Town's date of invoice.

OTHER USES

							CAPACITIES	5 <mark>2</mark>		SIZE DIA. ³ x HT.	
NUMBER	WATTS	VOLTS	AMPS	HERTZ	COOK TIM	RAW RICE	•	COOKED RICE	DI		
56822	_ 1700	120	14	60	31 minute	s 8 lb. (25	cups)	19 lb. (50 cup) 14¾"x 12"		
56824	_ 1500	230	7	_ 50/60_	44 minute	s 8 lb. (25	cups)	19 lb. (50 cup	s) 14	1¾″x 12″	
57137	_ 2160 <mark>¹</mark>	120	18	60	43 minute	s 13 lb. (37	cups)2	28 lb. (74 cup	s) 1 <i>5</i>	5¾"x 12¾"	
57138	1950	230	9	_ 50/60_	48 minute	s 13 lb. (37	cups)2	28 lb. (74 cup	s) 14	1¾"x 12¾"	
57155	3330	230	15			s 18 lb. (55		, ,	•	1¾"× 15½"	
¹ will never e	cceed 1800 w	atts				·		·			
NUMBER	LIQUID CA	APACITY	CARTO	N SIZE	CUBIC FEET	UNITS/CARTON	WT.	SHIP WT.	COLOR4	CORD LENGTH	
56822/4	11 qu	arts	_35" x 1	7" x 13"	4.2	2	15lb.	33 lb	mustard_	72″	
57137/8	13¼ (quarts	_18" x 1	8" x 15"	2.5	1	19lb.	22 lb	mustard_	72″	
57155	21½	quarts	_22" x 2	2" x 15"_	3.7	1	32lb.	36 lb	mustard_	72"	
¹ for better ric ² approximate	e, allow 10 ac	dditional min	utes for rice	to cure afte	r cooking						

IMPORTANT

CERTIFIED BY ETL/NSF TO NSF4/ANSI-4-COMMERCIAL COOKING, RETHERMALIZATION AND HOT FOOD EQUIPMENT-"SANITATION."

MINIMUM CLEARANCES- COMBUSTIBLE AND NON COMBUSTIBLE: Back Wall- 6" Left and Right Sides- 6" For use on non combustible floors only.

TOWN RESERVES THE RIGHT TO CHANGE DESIGN WITHOUT NOTIFICATION.

